

CRITICAL POWER CONFIDENCE.



CELLTRON ULTRA

UNIVERSAL STATIONARY BATTERY ANALYZER

Built upon experience and proven technology, the CELLTRON ULTRA offers advanced battery testing capabilities for effective evaluation and maintenance of all stationary power systems, including uninterruptible power supplies in Data Center environments with high levels of electrical interference noise.

Batteries have been demonstrated to be the “weakest-link” in most UPS systems, and historic methods for evaluation have been cumbersome, confusing and inconclusive. The CELLTRON ULTRA combines advanced conductance technology, state-of-the-art portable electronics, and convenient data management to facilitate fast, simple, safe and accurate battery management.



Franklin Electric

FEATURES:

- Enhanced conductance methodology enables accurate and repeatable testing in the presence of ultra-high electrical interference
- Software and data management techniques allow for the easy establishment of battery reference/baseline values when pre-determined data is not readily available allowing for "reference-free" testing
- The industry's first lighted probes increase visibility in confined battery cabinets and racks. This advance improves technician safety and test reliability while reducing risk of equipment damage
- Versatile multi-meter function allows for the measurement of AC & DC voltage and current. Scope mode displays AC ripple current and more
- Data on 12 battery manufacturers pre-loaded to expedite testing and record-keeping process
- CELLTRON ULTRA** stores over 250 pre-established reference/benchmark values to assist in the development of battery pass/fail thresholds
- CELLTRON ULTRA** includes two rechargeable battery packs—each providing power for more than 1000 full test sequences, or more than 16 hours of test time
- Complete kit provides everything needed for performing battery maintenance, including test probes and extenders, test clamps, temperature sensor, PC software and portable printer
- 32 megabyte card stores data up to 500 locations or systems



SPECIFICATIONS

MODEL NUMBER:

CTU-6000

APPLICATIONS:

Tests individual lead acid cells or monoblocs (up to 16 Volts) in any common configuration, approximately 10-6000 Ah.

VOLTAGE:

1.5 - 20.0 Volts DC

CONDUCTANCE:

100 - 19,990 Siemens

Test Data Storage:

500 string locations of 480 test results stored internally

ACCURACY:

+ 2% across test range

VOLTMETER RESOLUTION:

5 mV

USER PROGRAMMABLE FUNCTIONS:

- Preset values for over 250 battery types
- Low voltage alarm setting
- Low conductance warning
- Low conductance failure
- Test mode (push button/auto start)

CALIBRATION:

Auto-calibration prior to every test, no future calibration required

Connectorized Test

Cable Options:

- Dual contact clamps
- Dual contact probes
- Custom cables by quotation

POWER REQUIREMENTS:

9.6V, 1600mAh, NiMH
Internal swappable battery & charger

DISPLAY:

LCD - FSTN
2.619 in x 1.309 in, 128 x 64 pixels, 40 degree viewing angle, contrast ratio 8, Green LED backlight

KEYPAD:

Stainless-steel dome, polycarbonate overlay, 1,000,000 actuations

DATA TRANSFER:

Infra-red HP protocol, Infra-red, half-duplex IRDA protocol, RS-232 printer, Secure digital card

ENVIRONMENTAL OPERATING RANGE:

0 to +40 °C, 95% relative humidity, non-condensing

STORAGE TEMPERATURE:

-20 to 82 °C

Over Voltage Protection:

- Auto-reset disconnect
- Reverse polarity protected

HOUSING MATERIAL:

Acid resistant ABS plastic
santoprene overmold

ANALYZER DIMENSIONS:

11 in x 4 in x 3 in
280 mm x 105 mm x 80 mm

CASE DIMENSIONS:

19 in x 15.5 in x 7 in
485 mm x 395 mm x 180 mm

ANALYZER WEIGHT:

2.6 lb CTU-6000 Test Kit

SHIPPING WEIGHT:

Approximately 11 lb



Franklin Electric

STATIONARY POWER DEVICES

FRANKLIN ELECTRIC | GRID SOLUTIONS
7133 Monroe Street
Willowbrook, IL 60527

WWW.STATIONARY-POWER.COM
CUSTOMERSERVICE@FRANKLINGRID.COM
+1 844.344.5025

UTILITY GRID MONITORING

FRANKLIN ELECTRIC | GRID SOLUTIONS
34 Spring Hill Road
PO Box 638
Saco, Maine 04072

WWW.FRANKLINGRID.COM
INFO@FRANKLINGRID.COM
+1 800.225.9787

FIND US ON: 

